

GMI



ACTIVE-8 Gas Detection System



- Audible and Visual Alarms
- Common Low Level, Common High Level and Common Fault Relay Outputs as Standard
- Up to 16 Optional Relays for Customised Alarm Zoning
- Ability to Add More Channels if Required
- Easy Installation
- One Man Calibration



GMI - PROTECTING ENVIRONMENTS...WORLDWIDE

Active-8

The GMI Active-8 is an easy to use gas detection system which can house up to eight gas or fire input modules. These input modules can monitor a combination of different gas sensors and/or fire sensors, resulting in a flexible detection system designed for the smaller facility.

Flammable gases include Methane, Butane, Pentane, Propane, and Hydrogen. Toxic gases include Carbon Monoxide, Hydrogen Sulphide, Sulphur Dioxide, and also Oxygen.

Up to 30 fire and smoke detectors can be monitored per zone.

The alarm levels are programmable to give early warning of danger, these alarms are both audible and visual. There are two sounder outputs on the Active-8. The LCD will show the location of the alarm and any fault messages.

Features include up to 16 programmable relay outputs for customised alarm zoning and volt free outputs to drive external devices for both faults and alarms.

The Active-8 control panel is configured and calibrated using the 'Active-8-or' a hand-held communications adaptor that allows complete security for system settings and calibration information.

Gases

Flammable: Methane, Pentane, Propane, Butane, Hydrogen

Toxic: Carbon Monoxide, Hydrogen Sulphide, Sulphur Dioxide

Others: Oxygen (other gas types on request)

Relative Humidity Range

5% to 95% Non-Condensing

Fire Detection

Up to 30 Fire Detector per Zone

Number of Zones

Up to Eight Zones

Displays

Individual Zone LED Display

Common LED Display

Descriptive LCD Display

Alarms

Common Alarm 1, Alarm 2 and Fault

Terminals

Screw Type, Cable Sizes up to 4mm

Battery Options

Internal Battery Back-up (rating 1.2Ah) (optional)

Outputs

Alarm 1, Alarm 2, Fault

SPCO Relays with the following contact ratings:

Max Switching Power 60W

Max Switching Voltage 220vDC, 250vAC

Max Switching Current 2A

Two Monitored Sounder Outputs (rated at 24vDC 500mA each)

Dimensions:

415mm x 230mm x 102mm

Weight:

6.5Kgs (including batteries)

5.5Kgs (without batteries)

Power Supply:

240vAC, 110vAC or 24vDC

Inchinnan Business Park, Renfrew PA4 9RG, Scotland.

Tel: +44(0)141-812 3211 Fax: +44(0)141-812 7820

website: www.gmiuk.com

e-mail: sales@gmiuk.com

Service/Repair Centre:

25 Cochran Close, Crownhill,

Milton Keynes MK8 OAJ.

Telephone: 01908-568867. Fax: 01908-261056

As an ISO 9001:2000 approved company, GMI Ltd's quality assurance programmes demand the continuous assessment and improvement of all GMI products, Information in this leaflet could thus change without notification and does not constitute a product specification. Please contact GMI or their representatives if you require more details.



Distributor