

GMI



Single Point Gas Alarm Gas Detection System



- Compact Stand Alone Unit
- Simple to Integrate into Larger Systems
- Relay Outputs
- User Selectable Alarm Settings
- Easy Installation
- One Man Calibration
- 4-20mA



GMI - PROTECTING ENVIRONMENTS...WORLDWIDE

Gases

Flammable	0-100 %LEL
Hydrogen Sulphide	0-100ppm
Carbon Monoxide	0-100ppm
	0-500ppm
	0-1000ppm
Oxygen	0-25%
Other Gases on Request	

CONTROL PANEL**Size**

Height 230mm
Width 170mm
Depth 102mm

Weight

with battery 3.7kg
without battery 2.9kg

Terminals

Screw Types - Cable sizes up to 4mm

Degree of Protection

IP54

Power Supply

110x230v AC 50/60 Hz
24v DC

Display

1 Line 20 Digit LCD Display
(Backlit) 5 Status LED's

Operating Temperature Range

-10C + 40C

Relay Ratings

3 SPCO Relays rated 0.3 amp
at 240v AC

Humidity

5% - 95% RH Non Condensing

Alarm Settings

2 Levels adjustable
5% - 95% of range

Fault Detection

Open Circuit & Short Circuit
Line Fault Detection

OPTIONS

4-20mA Isolated Output
Panel Mounting Kit
Battery Back Up

Inchinnan Business Park, Renfrew PA4 9RG, Scotland.
Tel: +44(0)141-812 3211 Fax: +44(0)141-812 7820
website: www.gmiuk.com
e-mail: sales@gmiuk.com

Service/Repair Centre:
25 Cochran Close, Crownhill,
Milton Keynes MK8 OAJ.
Telephone: 01908-568867. Fax: 01908-261056

As an ISO 9001:2000 approved company, GMI Ltd's quality assurance programmes demand the continuous assessment and improvement of all GMI products, Information in this leaflet could thus change without notification and does not constitute a product specification. Please contact GMI or their representatives if you require more details.